### **FUOCOFREDDO**

Via Licinio Ferretti 5/A 43126 Parma (PR) C.F. / P.IVA 02669720340 Tel. 0521.1404565 info@fuocofreddo.it www.fuocofreddo.it

# OTTICA LED Alise 110



## **ALISE**

Aluminum reflectors in three different sizes with premium light quality for any track- or downlight luminaires. Suitable also for UV-C applications.

ALISE reflectors are made from aluminum and share the same clean and consistent look and beam variants throughout the entire product family. They have high heat resistance and offer premium light quality for any track- or downlight luminaires. With a wide range of compatible connectors and LEDiL original accessories, they are the most up-to-date reflector offering available.


#### ALISE-110

 $\emptyset$ 110 mm variant optimized for COBs with 22 mm LES size



### **PRODUCTS:**


## C16902\_ALISE-110-WW



Dimensions: 110.0 mm x 110.0 mm Height: 65.00 mm

~60° wide beam


C16901\_ALISE-110-W



Dimensions: 110.0 mm x 110.0 mm Height: 65.00 mm

~36° wide beam

## C16900\_ALISE-110-M



Dimensions: 110.0 mm x 110.0 mm

Height: 65.00 mm ~24° medium beam



# OTTICA LED Alise 110

**FUOCOFREDDO** 

Via Licinio Ferretti 5/A 43126 Parma (PR) C.F. / P.IVA 02669720340 Tel. 0521.1404565 info@fuocofreddo.it www.fuocofreddo.it

### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.


LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

## **PRODUCTS:**

### C16899 ALISE-110-S



Dimensions: 110.0 mm x 110.0 mm

Height: 65.00 mm ~15° spot beam